



TYPE II - UG2F06

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

TYPE



Country of Certification: CANADA
Ballistic Standard: NIJ 0101.06
NIJ Model: UG2F06
Threat Level: II
Areal Density: 0.83 lb/ft² (4.05 kg/m²)
Thickness: 0.18 in. (4.6 mm)
Composition: Spectra Shield® / Goldshield® Hybrid
Stitching: Shoulder tacks, bottom stitch
Ballistic Panel Cover: 200 denier Nylon Cover
 Polyurethane Backed
 Ultrasonically Welded Seams
 Patented Internal Desiccant
Ply Count: 31
NIJ 0101.06 Size Range: C1 to C5

BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1748 ft/s (533 m/s)	.357 Mag New V50	1648 ft/s (502 m/s)
9mm Conditioned V50	1683 ft/s (513 m/s)	.357 Mag Conditioned V50	1625 ft/s (495 m/s)
9mm BFS	29.8 mm	.357 Mag BFS	34.4 mm
9mm New RPI	2106.0	.357 Mag New RPI	1985.5
9mm Conditioned RPI	2027.7	.357 Mag Conditioned RPI	1957.8

EXAMPLE CARRIERS



Concealable



Premium Concealable



Clean Front



Tactical Response



Shirt Front



Tactical Patrol

Pacific Safety Products, Inc.

124 Fourth Avenue • Arnprior, ON K7S 0A9

TOLL FREE 1-888-997-9923 • FAX 613-623-6169

www.pacsafety.com



...we bring everyday heroes home safely.®