



NIJ 0101.06 TYPE IIIA-UG3AKXP

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

TYPE
IIIA

**NIJ
0101.06
CERTIFIED**



Country of Certification: CANADA
Ballistic Standard: NIJ 0101.06
NIJ Model: UG3AKXP
Threat Level: IIIA
Areal Density: 1.26 lb/ft² (6.16 kg/m²)
Thickness: 0.28" (7.1 mm)
Composition: Kevlar® Comfort XLT™ / Kevlar® XP™ Hybrid
Stitching: 1"x1" Diamond Quilt in Woven Fabric, Shoulder Box and Waist Tack
Ballistic Panel Cover: 200 denier Ripstop Cover Nylon Urethane Backed Ultrasonically Welded Seams Patented Internal Desiccant
Ply Count: 25
NIJ 0101.06 Size Range: C1 to C5

BALLISTIC PERFORMANCE AT CERTIFICATION

.357 Sig New V50	1914 ft/s (583 m/s)	.44 Mag New V50	1725 ft/s (526 m/s)
.357 Sig Conditioned V50	1890 ft/s (576 m/s)	.44 Mag Conditioned V50	1743 ft/s (531 m/s)
.357 Sig BFS	27.0 mm	.44 Mag BFS	36.4 mm
.357 Sig New RPI	1519.0	.44 Mag New RPI	1369.0
.357 Sig Conditioned RPI	1500.0	.44 Mag Conditioned RPI	1383.3

EXAMPLE CARRIERS



Concealable



Premium Concealable



Clean Front



Tactical Response



Shirt Front



Tactical Patrol

Pacific Safety Products, Inc.

124 Fourth Avenue • Arnprior, ON K7S 0A9

TOLL FREE 1-888-997-9923 • FAX 613-623-6169

www.pacsafety.com



...we bring everyday heroes home safely.®