

Country of Certification: CANADA
Ballistic Standard: NIJ 0101.06
Stab Standard: NIJ 0115.00
NIJ Model: MT2-S2XPL
Ballistic Threat Level: II
Stab Threat Level: Spike 2
Areal Density: 1.09 lb/ft² (5.3 kg/m²)
Thickness: 0.32 in. (8.1 mm)
Composition: Kevlar® Correctional/
Kevlar® XLT™ Hybrid
Stitching: Diamond Quilt, Shoulder Box, Top Stitch
Ballistic Panel Cover: 200 denier Nylon Cover, Polyurethane
Backed, Ultrasonically Welded Seams
Patented Internal Desiccant
Ply Count: 35
NIJ 0101.06 Size Range: C1 to C5



BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1572 ft/s (479 m/s)	.357 Mag New V50	1539 ft/s (469 m/s)
9mm Conditioned V50	1557 ft/s (475 m/s)	.357 Mag Conditioned V50	1551 ft/s (473 m/s)
9mm BFS	29.5 mm	.357 Mag BFS	35.3 mm
9mm New RPI	1429.0	.357 Mag New RPI	1399.0
9mm Conditioned RPI	1415.0	.357 Mag Conditioned RPI	1410.0

SPIKE RESISTANCE RATING

Protection Threat	Level 2	Energy Level 1 (E1)	24.3 ft-lbs/33 J
Protection Class	Spike	Energy Level 2 (E2)	36.9 ft-lbs/50 J

WARNING: This product is not intended to protect the wearer from commercially-made edged weapons, handgun or rifle fire.

EXAMPLE CARRIERS



Concealable



Premium
Concealable



Clean Front



Tactical
Response



Shirt Front



Tactical
Patrol

Pacific Safety Products, Inc.

124 Fourth Avenue • Arnprior, ON K7S 0A9

TOLL FREE 1-888-997-9923 • FAX 613-623-6169

www.pacsafety.com



...we bring everyday heroes home safely.®